

# CBR- Cut Back Remover

## *Technical Data Sheet*

### BENEFITS

- Effective on many adhesives such as cut back, most mastics, and other organic adhesives
  - Environmentally friendly, Bio-degradable
  - Non-Toxic, VOC compliant
  - Breaks Down and Emulsifies Cut Back Adhesive
- 

### Description:

CBR(Cut Back Remover) is a surface preparation solution that breaks down and emulsifies cut back adhesive on concrete and other cementitious surfaces.

**WARNINGS:** Do not allow to dry on the surface. Protect all adjacent surfaces from overspray. Thoroughly rinse product from surrounding vegetation. **CBR IS NOT MEANT TO BE AN ALTERNATIVE TO ASBESTOS MITIGATION. IF YOU ARE REMOVING AN ASBESTOS BASED ADHESIVE, FOLLOW PROPER ASBESTOS MITIGATION PROCEDURES.** While CBR is a safe product, it is still an aggressive cleaner. Long sleeves and gloves should be worn during application. Where spray back is possible eye protection should be worn. Should not be taken internally. Use in a well ventilated area. CBR is a safe effective cleaner with very low V.O.C.'s. It is water-based, environmentally friendly and Bio-Degradable. **KEEP OUT OF REACH OF CHILDREN.**

### COVERAGE:

Approximately 100 to 200 sq. ft per application per gallon, depending on surface soiling, porosity, density, and thickness of adhesive buildup.

### Application:

Read entire label before using. Use only as directed. Before applying, it is recommended that preliminary tests be carried out to determine usage and to test the effectiveness of the treatment. Apply solution liberally on surface to be prepped with a low pressure garden style pump sprayer or a plastic sprinkling can. Use a stiff bristled brush (nylon deck brushes are suggested) to lightly spread product

evenly over the surface, and allow solution to dwell for 10 minutes. After 10 minutes, agitate the surface with the stiff bristled brush in a back and forth motion going north to south and then east to west to assure complete surface agitation; areas of heavy buildup may require the use of a floor scraper to loosen thicker material. Allow the agitated solution to dwell on the surface an additional 10 minutes and rinse thoroughly. Allow surface to completely dry before analyzing results. Repeat process as needed.

**Disclaimer/Warranties:** Neither manufacturer nor seller have any knowledge or control concerning the purchaser's use of the product. No expressed warranty is made by manufacturer or seller with respect to the results of any use of the product or container that the product comes in. No implied warranties including, but not limited to, an implied warranty of merchantability or an implied warranty of fitness for a particular purpose are made with respect to the product. User shall rely on his or her own information and tests to be determine suitability of the product for the intended use and user assumes all risk and liability resulting from use of the product. Neither manufacturer nor seller assume any liability for personal injury, loss or damage resulting from the use of the product. We do not suggest or guarantee that any hazards listed herein are the only ones which may exist. In event that the product shall prove defective, buyer's exclusive remedy shall be that the seller or manufacturer shall, upon written request of buyer, replace any quantity of the product which is proven to be defective or shall, at its option, refund the purchase price of the product upon return of the product. Manufacturer shall not be responsible for use of this product in a manner to infringe on any patent held by others.