

VanHearron Inc. Technical Data

Inhance - Stages

WATER BASED COLOR ENHANCER AND STAIN RESISTANT SEALER

BENEFITS

- Enhances natural color
- Excellent water repellency
- Reduces staining
- Will not form a surface film or gloss
- Treated surfaces “breathe” and do not trap moisture
- Suitable for interior and exterior applications
- VOC compliant

DESCRIPTION

Inhance-Stages enhances the natural color of porous stone, pavers and other masonry while also providing excellent water repellency and resistance to staining. Inhance-Stages is a UV stable, penetrating treatment that provides long lasting protection and easy maintenance.

ALWAYS TEST each type of surface to ensure desired results. Let test area dry before inspection.

WARNINGS:

*****Inhance-Stages should not be used on polished or highly dense surfaces** (VanHearron’s Stain Guard 5000 sealer or Inhance Once and Done should be used for polished or dense substrates). Do not dilute or alter. Application temperature range 35° - 120°F (2° - 49°C). Protect from freezing. Inhance-Stages should be kept closed when not in use. Care should be taken to prevent moisture condensation in the container. May damage glass, aluminum, ceramics & glazed tile. Always protect. Protect people, vehicles, property, plants, windows, painted surfaces, anodized aluminum and all non masonry surfaces from product, splash, spray, residue, fumes and wind drift. Make sure all caulking and seals have fully cured before application. Surfaces should be clean and free of dirt, dust, oils and other contaminants. If necessary, clean with a recommended VanHearron surface preparation cleaner. Before using any chemical, read its label and Material Safety Data Sheet.

USAGE

Inhance-Stages can be used on most porous natural stone and masonry surfaces. VanHearron’s state-of-the-art protective treatments have developed a reputation by architects and building professionals as the premier solution for water repellents and sealers. VanHearron Inc. is dedicated to solving the destructive influence water intrusion and other elements have on building materials.

Vertical Application

Inhance-Stages should be applied by low-pressure (15 to 25 psi) pumping equipment with a wet fan type spray nozzle. Alternate methods include; nap roller (3/8 inch) or by brush.

Surfaces should be treated using a wet-on-wet technique by applying from the bottom up with six to eight inch run down from the bottom of the spray pattern. During application, precautions should be taken to protect the surrounding area from overspray and run off. Inhance-Stages will not etch glass but will leave a residue on non-porous surfaces.

Horizontal surfaces should be treated until material puddles or stands on the surface. Keep treated surface wet with Inhance-Stages for 3-5 minutes to ensure uniform penetration. Sweep, squeegee, or mop any remaining material to dry areas or wipe dry with clean towel. A second application may be applied to achieve a darker appearance. Allow first application to

dry 1 hour before proceeding with second coat.

CLEANUP

Clean equipment and overspray with soap and warm water.

COVERAGE

Follow recommended coverage rate guidelines.

Porous surfaces 50-100 sq. ft. /gal.

Semi-porous 100-125

Smooth 125-250

TECHNICAL SERVICE

Technical service engineers and chemists are available to answer questions on product performance, application methods and chemical composition.

AVAILABILITY

Inhance-Stages is available in 8oz, 16oz, 32oz, one gallon and five gallon containers.

This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of VanHearron Inc.'s knowledge or obtained from sources believed by VanHearron Inc. does not assume any legal responsibility for use or reliance upon same. Tests should be carried out only by chemists or chemically qualified lab technicians.

(479) 255-6101 www.vanhearron.com