

Sealer and Adhesive Remover

Technical Data Sheet

BENEFITS

- Effectively removes sealers, coatings and finishes.
- Long dwell time ideal for tough projects
- Cleans deep-set stains, epoxy grout haze, adhesives and paint
- Non-Flammable – Flash Point > 200° F

DESCRIPTION

A nonflammable, multipurpose stripper formulated to stay wet longer which gives the product time to remove most sealers, epoxy grout haze, urethane coatings, synthetic finishes, adhesives and paints. Also dissolves deep-set stains and removes heavy grease buildup.

Test application is recommended on surface to be treated to ensure compatibility and repellent result. Typical property values are not intended for use in the preparation of specifications. A test patch should be performed prior to general application with the customer's approval to ensure the desired appearance is achieved.

WARNINGS: MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN.

Wear skin and eye protection. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting, seek medical attention.

USE CHEMICAL-RESISTANT GLOVES, such as nitrile, when handling product.

USAGE: Natural stone (such as granite, limestone, marble, slate, and travertine), ceramic, porcelain, quarry, Saltillo, terra-cotta, cement pavers, and masonry surfaces

APPLICATION: **Do not spray apply product.** Surface should be free of standing water, dirt, dust, oils & other contaminants.

Surface Preparation: Read entire label before using. Provide good air ventilation to the room or area of application. Sweep or vacuum surface. Apply a liberal amount of Sealer and Adhesive Remover to a small, manageable area of up to 25 ft (2 M). Spread with a mop or brush. Allow product to dwell up to 1 hour without drying or until coating or residue softens. Do not allow Sealer and Adhesive Remover to dry on surface - if remover starts to dry, add more to ensure surface is kept wet. Agitate with a scrub brush or scrub machine. Wipe up residue with clean, absorbent white cotton towels. A

wet/dry vacuum may be used. Removal of thick coatings or residue may require several applications - repeat steps 3 through 7 if coating is still on surface. Rinse thoroughly with clean water. Ready for surface traffic in 1 hour or after surface is dry to the touch. Allow at least 24-hour drying time before applying **Sealer and Adhesive Remover**.

CLEAN UP: Thoroughly rinse application equipment with water before material dries.

STORAGE: Close container tightly after each use

Store in original container only

Store in and use in temperatures between 45° F to 85° F (7.2° C to 29.4° C)

Store in areas inaccessible to small children

Do not reuse empty container, wrap and discard in trash or recycle

COVERAGE: 200– 2000 sq ft per gallon depending on surface porosity, density and desired finish

Contact VanHearron Technical Services for further information or application instructions.

Disclaimer/Warranties: Neither manufacturer nor seller have any knowledge or control concerning the purchaser's use of the product. No expressed warranty is made by manufacturer or seller with respect to the results of any use of the product or container that the product comes in. No implied warranties including, but not limited to, an implied warranty of merchantability or an implied warranty of fitness for a particular purpose are made with respect to the product. User shall rely on his or her own information and tests to be determine suitability of the product for the intended use and user assumes all risk and liability resulting from use of the product. Neither manufacturer nor seller assume any liability for personal injury, loss or damage resulting from the use of the product. We do not suggest or guarantee that any hazards listed herein are the only ones which may exist. In event that the product shall prove defective, buyer's exclusive remedy shall be that the seller or manufacturer shall, upon written request of buyer, replace any quantity of the product which is proven to be defective or shall, at its option, refund the purchase price of the product upon return of the product. Manufacturer shall not be responsible for use of this product in a manner to infringe on any patent held by others.