

# VanHearron Inc. Technical Data

## Grout Once!

*SELF SEALING ADD MIX FOR GROUT*

### **BENEFITS**

- Integrated seal with no need for topical application.
- Environmentally friendly, low VOC (less than 9 g/l)
- Reduction in water absorption reduces cracking due to freeze-thaw and efflorescence
- Penetrating treatment will not change appearance or adhesion properties.
- Mildew and Fungus Resistant
- Non-Flammable – Flash Point > 200° F
- Low Odor
- Reduces adhesion failures due to water penetration

### **DESCRIPTION**

One-component, VOC compliant, add mix for grout and mortar. Mixes with grout **INSTEAD OF WATER**, for an integrated seal, creating a sealed harder, denser, stain resistant grout, without the need for topical application.

### **WARNINGS:**

**Do not dilute or alter. Protect from freezing.** Use eye protection and minimize skin contact with gloves and clothing. Do not smoke in vicinity of application. Do not store or use near sparks or open flames.

### **USAGE**

Can be used with most grout dry mixes **INSTEAD OF WATER**.

### **INSTRUCTIONS:**

**Shake well before using.** Ensure that you are using cement based grout. Follow Manufacturers instructions for mixing grout using Grout Once! **INSTEAD OF WATER**. Empty contents of grout package into a clean bucket and dry mix the grout, THEN add ¾ of the corresponding bottle and mix thoroughly, then slowly add the remainder of the liquid **AS NEEDED** to achieve the desired consistency. If mix is too dry it is acceptable to add up to 3 ounces of clean tap water. It is absolutely imperative when using Grout Once! That the grout be allowed slake 5-7 minutes and then be thoroughly mixed again as suggested by the grout manufacturer. Clean up as per grout manufacturer's instructions using **AS LITTLE WATER AS POSSIBLE**.

### **DRY TIME:**

Dry time is consistent with the specifications on the particular grout used, and is unaffected as compared to water mix.

**COVERAGE:** Mixes 30-40 pounds of dry grout per gallon. One 70 oz. bottle does approximately one 25 pound bag of sanded grout. One 48 oz. bottle does approximately one 10 pound box of unsanded grout. One 27 oz. bottle does approximately one 10 pound bag of sanded grout.

**Contact VanHearron Technical Services for further information or application instructions.**

Disclaimer/Warranties: Neither manufacturer nor seller have any knowledge or control concerning the purchaser's use of the product. No expressed warranty is made by manufacturer or seller with respect to the results of any use of the product or container that the product comes in. No implied warranties including, but not limited to, an implied warranty of merchantability or an implied warranty of fitness for a particular purpose are made with respect to the product. User shall rely on his or her own information and tests to be determine suitability of the product for the intended use and user assumes all risk and liability resulting from use of the product. Neither manufacturer nor seller assume any liability for personal injury, loss or damage resulting from the use of the product. We do not suggest or guarantee that any hazards listed herein are the only ones which may exist. In event that the product shall prove defective, buyer's exclusive remedy shall be that the seller or manufacturer shall, upon written request of buyer, replace any quantity of the product which is proven to be defective or shall, at its option, refund the purchase price of the product upon return of the product. Manufacturer shall not be responsible for use of this product in a manner to infringe on any patent held by others.

**Phone: (479) 255-6101 [www.vanhearron.com](http://www.vanhearron.com)**